


Product Specifications for E21301-10Po	Product	Specifications '	for E	21301	-10P0
--	---------	------------------	-------	-------	-------

•	Toddot opcomoditorio for E2 foot for o			
	Job Name:	Job Type:		
	Quantity:	Comments		



E21301-10PC Inca 9-Light Flush Mount



Finish Polished Chrome

Lamping

Number of Bulb(s) **Light Type** Xenon **Bulb Type** G9 Max Bulb Wattage 40 **Max Fixture Wattage** 360 **Rated Life** ±2,000 Hours **Rated Lumens** ±4,500 Color Temp ±2,900 K Bulb(s) Included Yes Light Up/Down **Beam Spread** N/A N/A **Photo Cell Included** N/A Ballast/Driver/Transformer No **Dimmable** Standard

Glass/Shade Clear/White

Other

UPC Code

Material

Measurements Width 23.50" Height 8.75" Length N/A Extension N/A **Back Plate Width** N/A **Back Plate Height** N/A **HCO** N/A Min Overall Height N/A Max Overall Height N/A Hanging Weight 14.74 lb(s) **Height Adjustable** N/A Slope N/A Chain Length N/A Wire Length N/A **Canopy Width** N/A Canopy Height N/A Canopy Length N/A

Product Category

Flush Mount

Shipping	
Carton Weight	20.68 lb(s)
Carton Width	27.56"
Carton Height	11.82"
Carton Length	27.56"
Carton Cubic Feet	N/A
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Safety Rating	Dry
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No

Equivalents

845094032748

Metal

Incandescent Watts	N/A
Fluorescent Watts	N/A

ET2 Contemporary Lighting and all designs, logos and images © 2015 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.