

# HALO

Design by Martin Azua.

## Reference

**2361.**

## Application

Wall Fixtures

## Installation type

Surface mounted

## Description

Wall sconce. The light rods, anchored to an aluminum profile are arranged around a central perpendicular axis, in parallel or angled. The modular character allows for large interconnected lights murals to be configured.

## Diffuser

PMMA diffuser

## Materials

Diffuser: Acrylic

LED support: Aluminum

Wall support: Aluminum

## Finishes




**2361-11** Black (NCS S 8500N)



**2361-13** Grey L1 (NCS S 1000-N)

## Sketch



## Electrical characteristics

1 x LED STRIP 24V 15,3W

Total 15.3 W



# VIBIA



**Light source:** 3000K CRI >80 4584.12 lm 99.87 lm/W

**Fixture:** 3472.02 lm 75.64 lm/W

**Driver included:** CV - Constant Voltage 120-277V 50/60Hz

**Electronic dimming:** NO DIMMING

## Technical characteristics

- Surface Mounted


## Installation and assembly

Please see the installation manual

## Light distribution

### General lighting

Lamp for general lighting that equally distributes the light in all directions.



## Photometric data

Efficiency : 100 %

Coordinate system : CG

Total flux : 3466.15 lm

Maximum value : 580.67 cd

Light position : C=180.00 G=70.00

Symmetry on the planes : Asymmetrical

Isolux : Floor

Light position :

X=0.00m Y=0.00m Z=2.50m

## Certificates

