


Product S	Specifications	for	F32770	-91RC

Job Name:	Job Type:
Quantity:	Comments



# E32770-91BC **Scepter 1-Light Wall Sconce**



\*height from center of outlet to the top of the fixture

## **Finish Black Chrome**

## Lamping

#### Number of Bulb(s) **Light Type** LED **Bulb Type** LED Max Bulb Wattage 7.5 **Max Fixture Wattage** 7.5 **Rated Life** N/A **Rated Lumens** ±246 **Color Temp** ±3,000 K Bulb(s) Included Yes Light Up/Down N/A **Beam Spread** N/A N/A **Photo Cell Included** N/A Ballast/Driver/Transformer No Standard/Lutron® **Dimmable** CL or Leviton® LED Recommended

## Glass/Shade Bubble

# Measurements

wedsurements	
Width	4.50"
Height	19.00"
Length	N/A
Extension	5.50"
Back Plate Width	N/A
Back Plate Height	N/A
HCO	7.00"
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	3.06 lb(s)
Height Adjustable	Yes
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

# **Product Category**

Wall Sconce

### Shippina

Unipping	
Carton Weight	4.17 lb(s)
Carton Width	8.00"
Carton Height	7.75"
Carton Length	15.50"
Carton Cubic Feet	N/A
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

# Certification

Safety Rating	Dry
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No

# Other

UPC Code	845094077145
Material	Metal+Glass

## **Equivalents**

incandescent watts	N/A
Fluorescent Watts	N/A

ET2 Contemporary Lighting and all designs, logos and images © 2016 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.