


Product Specifications for E32775-91BC

-	Job Name:	Job Type:
	Quantity:	Comments



E32775-91BC **Scepter 5-Light Pendant**



Finish

Black Chrome

Lamping	
Number of Bulb(s)	5
Light Type	LED
Bulb Type	LED
Max Bulb Wattage	7.5
Max Fixture Wattage	37.5
Rated Life	N/A
Rated Lumens	±1,230
Color Temp	±3,000 K
Bulb(s) Included	Yes
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A

Rated Lumens	±1,230
Color Temp	±3,000 K
Bulb(s) Included	Yes
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard/Lutron® CL or Leviton® LED Recommended

Glass/Shad	ŧ
Bubble	

Measurements	
Width	13.00"
Height	18.00"
Length	13.00"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	140.00"
Hanging Weight	10.91 lb(s)
Height Adjustable	Yes
Slope	N/A
Chain Length	N/A
Wire Length	N/A
0 145 141	N 1/A
Canopy Width	N/A
Canopy Height	N/A

Product Category Multi-Light Pendant

Shipping	
Carton Weight	13.67 lb(s
Carton Width	16.00
Carton Height	7.50
Carton Length	18.50
Carton Cubic Feet	N/A
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Safety Rating	Dr
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No

Other

Canopy Length

845094077220
Metal+Glass

Equivalents

N/A

Incandescent Watts	N/A
Fluorescent Watts	N/A

ET2 Contemporary Lighting and all designs, logos and images © 2016 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.