

## UMBRELLA BASE GUIDE **BY APPLICATION**

- **TABLE USE:** Indicates the base is suitable for use beneath a table. It is not recommended as a free-standing base option.
- **FREE-STANDING:** Indicates the base is recommended as a free-standing option, but also suitable for use beneath a table if the table provides enough clearance to safely sit above the base on a flat surface. 18" (18ST/2) Stems should always be used when in this application.
- **1.5"/38mm STEM:** Indicates the base can accommodate a 1.5"/38mm center pole.
- **2"/50mm STEM:** Indicates the base can accommodate a 2"/50mm (18ST2) center pole.

	7.5' OCT. / 2.3m	9' OCT. / 2.7m	11' OCT. / 3.5m	13' OCT. / 4m	6.5' SQ. / 2m	7.5' SQ. / 2.3m	10' SQ. / 3m	8' X 10' REC. / 3m	8.5' X 11' REC. / 3.5m
<b>ALUMINUM SHELL</b>									
502A	● ●				● ●				
<b>RESIN COATED</b>									
50C	● ●	● ●	● ●		● ●	● ●		● ●	
23	● ●	● ●	● ●		● ●	● ●		● ●	
<b>ALUMINUM CONCRETE</b>									
100A	● ● ●	● ● ●	● ● ●		● ● ●	● ●		● ●	
150A	● ● ●	● ● ●	● ● ●	● ●	● ● ●	● ● ●	● ●	● ● ●	● ●
<b>STEEL PLATE</b>									
50S	● ●	● ●	● ●		● ●	● ●		● ●	
75S	● ●	● ●			● ●				
<b>GALVANIZED STEEL</b>									
24G	● ● ●	● ● ●	● ●		● ● ●	● ●		● ●	
30G	● ● ●	● ● ●	● ● ●		● ● ●	● ● ●		● ● ●	
36G	● ●	● ●	● ●	● ●	● ●	● ●	● ●	● ●	● ●
40G	● ●	● ●	● ●	● ●	● ●	● ●	● ●	● ●	● ●
20G-SQ	● ● ●	● ●	● ●		● ●	● ●		● ●	
24G-SQ	● ● ●	● ● ●	● ● ●		● ● ●	● ● ●		● ●	
36G-SQ/ +W	● ●	● ●	● ●	● ●	● ●	● ●	● ●	● ●	● ●
<b>WHEEL BASE</b>									
ARU/ECU/G-480	● ●	● ●	● ●	● ●	● ●	● ●	● ●	● ●	● ●

**NOTE:** 18" stems (18ST/2) are recommended for free-standing applications. Frankford will not recommend a free-standing application with a shorter stem. The 75S (16" stem) is considered a free-standing base as noted above.